

MICRO ANALYTICAL LABORATORIES, INC.

PHASE CONTRAST MICROSCOPY

1122
C & W Environmental Consulting
2532 Santa Clara Avenue
PMB 390
Alameda, CA 94501

PROJECT:
COUNTY OF MONTEREY
SUPERIOR COURTHOUSE
NORTH WING
240 CHURCH STREET
SALINAS, CA

Micro Log In **86667**
Total Samples 7
Date Sampled 09/05/2006
Date Received 09/06/2006
Date Analyzed 09/06/2006

Sample ID	Field Data	Lab Data	Fibers / cc	Limits	
Client: COM-9506-R1-1 Micro: 86667-01 KS THIRD FLOOR COURT HALL BY JURY ROOM	Time 400 Rate 4.0 Liters 1600.0	Fibers 19 Fields 100 F/mm ² 24.2	0.006	LCL 0.002 LOD 0.002 CV	UCL 0.009 LOQ 0.024 0.30
Client: COM-9506-R1-2 Micro: 86667-02 THIRD FLOOR MEZZANINE BY WATER FOUNTAIN	Time 399 Rate 4.0 Liters 1596.0	Fibers 58 Fields 100 F/mm ² 73.9	0.018	LCL 0.008 LOD 0.002 CV	UCL 0.028 LOQ 0.024 0.28
Client: COM-9506-R1-3 Micro: 86667-03 FIRST FLOOR LOBBY AT WATER FOUNTAIN	Time 409 Rate 4.0 Liters 1636.0	Fibers 56.5 Fields 100 F/mm ² 72.0	0.017	LCL 0.008 LOD 0.002 CV	UCL 0.026 LOQ 0.024 0.28
Client: COM-9506-R1-4 Micro: 86667-04 FIRST FLOOR COURT HALL AT JURY ROOM	Time 411 Rate 4.0 Liters 1644.0	Fibers 22 Fields 100 F/mm ² 28.0	0.007	LCL 0.003 LOD 0.002 CV	UCL 0.010 LOQ 0.023 0.30
Client: COM-9506-R1-5 Micro: 86667-05 BASEMENT NORTH CORRIDOR AT MECH. ROOM	Time 425 Rate 4.0 Liters 1700.0	Fibers 21 Fields 100 F/mm ² 26.8	0.006	LCL 0.002 LOD 0.002 CV	UCL 0.010 LOQ 0.023 0.30

Technical Supervisor: _____

Frank Raviola, M.S.

9/6/2006

Date Reported

Analyst: _____

KS

AIHA IHLAP Laboratory Accreditation / PAT ID No. 101768. Samples are analyzed using the NIOSH 7400 Method (NIOSH Manual of Analytical Methods, 4th Ed., Issue 2 of Rev. 3, 8/15/1994). The "A" Rules are used, unless otherwise noted. The limit of detection (LOD) is 7 fibers/mm². Limits of quantification for optimal precision and accuracy are 100 (LOQ) and 1300 fibers/mm². The 95% UCL and LCL (Upper and Lower Confidence Limits of the Two-sided 95% Confidence Interval) represent the highest and lowest expected concentrations (in fibers/cc) for a given fiber count, based on the reported concentration. Intralaboratory coefficients of variation (CV) for various fiber loadings are reported. Limits for compliance testing may be calculated by the client, using the CV and an appropriate regulatory standard, e.g. UCL = (Concentration + [1.645 x CV x Standard]). Concentrations are field blank-corrected. Time is in minutes, flow rate is in liters per minute. 8 Hour TWA: calculated time weighted average concentration (in fibers/cc) based on 8 hours. Note: due to method variability, 95% LCL and UCL for the TWA may vary significantly from reported TWA values. The 8 hour TWA may not be statistically accurate for actual total times less than 8 hours; zero concentration is assumed for remaining time if no information is given. Micro Analytical Laboratories, Inc. assumes no responsibility for clients' interpretation of any requested TWA data or calculations in this report. Unless otherwise indicated on this report, all required Quality Control samples have been determined to be in control prior to releasing these analytical results. This report must not be reproduced except in full, with the approval of Micro Analytical Laboratories, Inc., and pertains only to the samples analyzed. Unless otherwise stated in this report, all samples were received in acceptable condition for analysis. Micro Analytical Laboratories, Inc. shall not be responsible for clients' deviations from any prescribed sampling parameters. Air volumes are based on client data. The laboratory's verifiability of results is limited to fibers per mm². N/A = not applicable.

MICRO ANALYTICAL LABORATORIES, INC.

PHASE CONTRAST MICROSCOPY


1122
C & W Environmental Consulting
2532 Santa Clara Avenue
PMB 390
Alameda, CA 94501

PROJECT:
COUNTY OF MONTEREY
SUPERIOR COURTHOUSE
NORTH WING
240 CHURCH STREET
SALINAS, CA

Micro Log In **86667**
Total Samples 7
Date Sampled 09/05/2006
Date Received 09/06/2006
Date Analyzed 09/06/2006

Sample ID	Field Data	Lab Data	Fibers / cc	Limits	
Client: COM-9506-R1-6 Micro: 86667-06 FIELD BLANK	Time Rate Liters	Fibers 0 Fields 100 F/mm ² < 7.0		LCL	UCL
				LOD	LOQ
				CV	0.60
Client: COM-9506-R1-7 Micro: 86667-07 SEALED BLANK	Time Rate Liters	Fibers 0 Fields 100 F/mm ² < 7.0		LCL	UCL
				LOD	LOQ
				CV	0.60

Technical Supervisor: _____




Frank Raviola, M.S.

9/6/2006
Date Reported

Analyst: _____

KS

AIHA IHLAP Laboratory Accreditation / PAT ID No. 101768. Samples are analyzed using the NIOSH 7400 Method (NIOSH Manual of Analytical Methods, 4th Ed., Issue 2 of Rev. 3, 8/15/1994). The "A" Rules are used, unless otherwise noted. The limit of detection (LOD) is 7 fibers/mm². Limits of quantification for optimal precision and accuracy are 100 (LOQ) and 1300 fibers/mm². The 95% UCL and LCL (Upper and Lower Confidence Limits of the Two-sided 95% Confidence Interval) represent the highest and lowest expected concentrations (in fibers/cc) for a given fiber count, based on the reported concentration. Intralaboratory coefficients of variation (CV) for various fiber loadings are reported. Limits for compliance testing may be calculated by the client, using the CV and an appropriate regulatory standard, e.g. UCL = (Concentration + [1.645 x CV x Standard]). Concentrations are field blank-corrected. Time is in minutes, flow rate is in liters per minute. 8 Hour TWA: calculated time weighted average concentration (in fibers/cc) based on 8 hours. Note: due to method variability, 95% LCL and UCL for the TWA may vary significantly from reported TWA values. The 8 hour TWA may not be statistically accurate for actual total times less than 8 hours; zero concentration is assumed for remaining time if no information is given. Micro Analytical Laboratories, Inc. assumes no responsibility for clients' interpretation of any requested TWA data or calculations in this report. Unless otherwise indicated on this report, all required Quality Control samples have been determined to be in control prior to releasing these analytical results. This report must not be reproduced except in full, with the approval of Micro Analytical Laboratories, Inc., and pertains only to the samples analyzed. Unless otherwise stated in this report, all samples were received in acceptable condition for analysis. Micro Analytical Laboratories, Inc. shall not be responsible for clients' deviations from any prescribed sampling parameters. Air volumes are based on client data. The laboratory's verifiability of results is limited to fibers per mm². N/A = not applicable.



C&W Environmental Consulting, Inc.

CHAIN OF CUSTODY

86667
PCM

Project: _____

Client: County of Monterey - Abert's Wine Courthouse Sampling Date: 9/15/06

Site Address: 240 Church St, Salinas CA Page (s): 1 of 1

Turnaround Time: Asap

ID	Analysis	Description	Start Time	Stop Time	Total Time	Average LPM	Total Liters	Pore Size
CM-9316-R1-1	PCM	3/F COURT HALL BY JURY ROOM	04:00	10:40		4.0		.8
-2		3/F MEZANINE BY WATER FOUNTAIN	04:00	10:39		4.0		
-3		1/F ENTRY AT WATER FOUNTAIN	04:00	10:49		4.0		
-4		1/F COURT HALL AT JURY ROOM	04:00	10:51		4.0		
-5	PCM ^{Yarned}	BASEMENT - N. CORRIDOR AT MECH. ROOM	04:00	11:05		4.0		
-6		FIELD BLANK	:	:				
-7		SEALED BLANK	:	:				
			:	:				
			:	:				
			:	:				
			:	:				

Additional Notes:

Relinquished by: [Signature] Date & Time: 9/15/06

Relinquished by: [Signature] Date & Time: 9/15/06 12:44

Relinquished by: [Signature] Date & Time: 9/15/06 2:44

Relinquished by: [Signature] Date & Time: 9/16/06 2:15 AM